CUSTOMER

Control humidity with Quality, high-pressure fog systems. Excellent Customer Support and Green* technology...with COLD FOG®

Quality is important! We build COLD FOG systems to be ready to start-up at the jobsite, right out of the crate! Factory tested and totally pre-wired; just attach electrical power and your potable water supply to our regulator. No adjusting, no belts, no pulleys and no problems! "Soft-start" feature on every start-up for quiet, vibration-free operation with no electrical surge ever!

COLD FOG® systems automatically come up to the needed minimum speed to maintain your preselected fog pressure! Regardless of how many nozzles fogging, the system will sense, control and maintain the lowest possible RPM's. Lower speeds reduce wear, noise and pump maintenance and power. Always quiet, always reliable.....

COLD FOG is a Registered Trademark of Atomizing Systems Inc., U.S.A.

Slow-speed, quiet running
Smooth, rigid direct-drive
All stainless pump-base
Water-tight & water-proof
Finger-safe electronics
20% built-in expansion capability
Full Tech Manual Documentation
Remote start circuit built-in
Complimentary start-up spares



A T O M I Z I N G S Y S T E M S I N C • Efficient to operate with slow-speed "SOFT-START"

- Patented Ruby-orifice nozzle technology
- Never wear-out another nozzle (25 year Warranty)
- Choose from 9 Nozzle sizes available from stock
- Control accuracy available to ±1%



Length: 28 inch (71cm) Width: 20 inch (51cm) Height: 48 inch (122cm)

- 13 to 88* nozzles
- 6 different flow rates
- 50 or 60 hertz
- I/2 to 2 horsepower
- 120vac to 460vac



*no compressed air

Phone: 201.447.1222 Fax: 201.447.6332 E-mail: info@coldfog.com Atomizing Systems Inc 1 Hollywood Avenue Ho-Ho-Kus, New Jersey 07423 U.S.A.